



SEARCH

Go

[Product Type](#)


[Part Number](#)

[Product Name](#)

[Competitor](#)

- [English](#)
- [Español](#)
- [Français](#)
- [Italiano](#)
- [Deutsch](#)
- [Polski](#)
- [Português](#)
- [По Русски](#)
- [中文显示](#)
- [日本語](#)
- [한국어](#)

Datasheet
Crimp Housings




- [10-01-4034](#)
- [Datasheet](#)
- [Product Specification \(PDF\)](#)

[[Home](#) > [Products](#) > [Crimp Housings](#) > [Datasheet](#)]

[Print](#)

10-01-4034

2.00mm (.079") Pitch Micro SPOX™ Wire-to-Board Housing, 3 Circuits



[View all parts in series 5231](#)

[E-mail this page](#)

ENVIRONMENT

[RoHS Status](#)

ELV and RoHS Compliant

Features and Benefits

- Housing lance ensures good terminal retention

Status	INACTIVE / OBSOLETE
Circuits / Positions	3
Pitch / Center Spacing	2.00mm (.079")
Rows	1
Product Name	SPOX™
Gender	Female
Stackable	No
Wire Entry Angle	Vertical
Panel Mount	No

RELATED PRODUCTS

Mates With	5233
Use With	5230
Contact Insertion Force-max. (per circuit)	9.8N (2.2 lb)
Contact Retention Force-min. (per circuit)	14.7N (3.30 lb)

PHYSICAL

Housing Material	PA Polyamide (Nylon) 6/6
Flammability	UL 94V-0
Temperature Range	-20°C to +85°C
Designed In	Millimeters
Unmated Height	8.00mm (.315")

Unmated Width	5.90mm (.232")
REFERENCE	
Product Specification	PS-5231-001
Packaging	Bag
UL File Number	E29179
Old Part Number	5231-03
Molex Series	5231

For all product dimensions, please refer to Drawing (PDF).

© Copyright 2005 Molex Incorporated