


SPECIFICATION TYPE : 12VX



Customer.
 Customer's Dwg. Number _____ Rev. _____
 Customer's Part Number _____
 Toko Sample Number 707VX-A062AO


Approved by _____
 Signature _____ Date _____

One copy with your signature is required as your confirmation to our Specifications.



	Customer's Specifications	Toko's Specifications
Center Frequency (Fc)		23kHz
Tuning Range (1 - 3)		1.0mH ± 6% at 252kHz
Unloaded Q (1 - 3)	—	50 min at 252kHz

Marking	Customer's Specifications		Toko's Specifications	
	Number of turns	Wire(mm)	Number of turns	Wire(mm)
			1 - 3	228
			4 - 6	91
				0.12



Dielectric With Standing Voltage.
 Samples shall be subjected to 100V DC between primary and secondary.
 Samples should have no apparent defects.

Insulation Resistance.
 Samples shall be subjected to 100V DC between primary and secondary.
 Insulation resistance should be greater than 100 MΩ.

Notes 1. Above sample is modified from Toko Sample No.

Approved by:	Checked by:	Made by:	Orig	07-APR-1999	Issues	Sign
H. OHTSUKA	LAI HO CHING	LAI WAI CHUN				

45, Hoi Yuen Road, Yau Lee Centre, 8/F.,
 Kowloon, Hong Kong

TOKO, INC.
 HONG KONG BRANCH
 TOTAL P.02