



TECHNICAL CHARACTERISTICS :

- Female screw locks: brass, tin lead
- Compensating washer: steel, tin lead
- Nuts : steel, tin lead
- Packaging : per 100 pieces .
- Corrosion resistance : 50 hour .

NOTE:RoHS INFORMATIONS

- The "LF" products meet European union Directives and other country regulations as described in GS-22-008.
- Plating Sn (pure bright) over copper
- Packaging spec: see 65-14-920

LEAD FREE NUMBER 863001TLF PACKAGING:per 100 pieces

www.fciconnect.com		surface ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection A3	mm
TOLERANCES UNLESS OTHERWISE SPECIFIED					
ANGULAR	LINEAR	0.X	±0.1	size A3	Scale 10
0.XX	±2'	0.XX	±0.1	ECN LS09-0063	
0.XXX		0.XXX	±0.1	Spec ref -	
Product family	D-SUB				
Dr	JOUBERT	1996/01/28			
Eng	JOUBERT	1996/01/28			
Chr	LEGARE	1996/01/28			
Appr	LEGARE	1996/01/28			
rev	ecn no	dr	date		
B	-	SBA	2003/04/15		
C	LS05-0026	LMA	2005/02/09		
D	-	-	-		
E	LS06-0097	LGO	2006/07/28		
F	LS09-0006	PCR	2009/01/08		
G	LS09-0063	PCR	2009/03/25		
-	-	-	-		
title FEMALE SCREW LOCK		dwg no C01-8655-0698		Rev. G	
D SUB ACCESSORIES		CUSTOMER		sheet 1 of 1	
catalog no					

Copyright FCJ. FCJ