

## Technical Data:

### CP-TIM-201-3D-650

<b>Wavelength:</b>	650nm
<b>Output Power:</b>	<3mW (Continuous Wave)
<b>Operating Voltage:</b>	3V DC
<b>Operating Current:</b>	30~50mA
<b>Class:</b>	IIIA
<b>Divergence:</b>	<2mrad
<b>Laser Head Case:</b>	Copper (DC+)
<b>Operating Temp. Range:</b>	14°F - +77°F -10°C - +25°C
<b>Storage Temp. Range:</b>	-40°F - +170°F -40°C - +80°C
<b>Housing:</b>	Brass
<b>Housing Dimensions:</b>	32.5mm x 10.5mm
<b>Wire Length:</b>	250mm

### CP-TIM-201-5D-650

<b>Wavelength:</b>	650nm
<b>Output Power:</b>	<5mW (Continuous Wave)
<b>Operating Voltage:</b>	3V DC
<b>Operating Current:</b>	30~50mA
<b>Class:</b>	IIIA
<b>Divergence:</b>	<2mrad
<b>Laser Head Case:</b>	Copper (DC+)
<b>Operating Temp. Range:</b>	14°F - +77°F -10°C - +25°C
<b>Storage Temp. Range:</b>	-40°F - +170°F -40°C - +80°C
<b>Housing:</b>	Brass
<b>Housing Dimensions:</b>	32.5mm x 10.5mm
<b>Wire Length:</b>	250mm