



BIPOLAR

NPN MESA POWER TRANSISTORS

PACKAGE	DEVICE TYPE	V_{CE0} VOLTS	PEAK I_C AMPS	h_{FE} min/max	$I_C @ V_{CE}$ A V	V_{CE} (sat) max VOLTS	$I_C @ I_B$ A A
T0-204 (T0-3) 	2N3715*	60	10.0	50-150	1.0/2.0	0.8	5.0/0.5
	2N3716*	80	10.0	50-150	1.0/2.0	0.8	5.0/0.5
	2N3902*	325	2.5	30-90	1.0/5.0	0.8	1.0/0.1
	2N5302*	60	30.0	15-60	15.0/2.0	1.7	15.0/2.0
	2N5303*	80	20.0	15-60	10.0/4.0	1.5	10.0/2.0
	2N5685*	60	50.0	15-60	25.0/2.0	1.0	25.0/2.5
	2N5686*	80	50.0	15-60	25.0/2.0	1.0	25.0/2.5
	2N6249*	225	10.0	10-50	10.0/3.0	1.5	10.0/1.0
	2N6250*	300	10.0	8-50	10.0/3.0	1.5	10.0/1.25
	2N6251*	375	10.0	6-50	10.0/3.0	1.5	10.0/1.67
T0-63 	2N3846*	200	20.0	40 min	5.0/5.0	0.75	10.0/1.0
	2N3847*	300	20.0	40 min	5.0/5.0	0.75	10.0/1.0

• Electrical Characteristics at 25° C unless otherwise noted

* Available in JANTX & TXV