

CMOS 4-Bit Microcontroller

**TMP47P400VN**  
**TMP47P400VF**



The TMP47P400V is the system evaluation LSI of TMP47C200B/400B with 32K bits one-time PROM. The TMP47P400V programs / verifies using an adapter socket to connect with PROM programmer, as it is in TMM2764AD.

In addition, the TMP47P400V and the TMP47C200B/400B are pin compatible. The TMP47P400V operates as the same as the TMP47C200B/400B by programming to the internal PROM.

Part No.	ROM	RAM	Package	Adapter Socket
TMP47P400VN	OTP	256 x 4-bit	P-SDIP42-600-1.78	BM1118
TMP47P400VF	4096 x 8-bit		P-QFP44-1414-0.80D	BM1125

Pin Assignment (Top View)

P-SDIP42-600-1.78





000707EBA1

- For a discussion of how the reliability of microcontrollers can be predicted, please refer to Section 1.3 of the chapter entitled Quality and Reliability Assurance / Handling Precautions.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

Pin Assignment (Top View)

P-QFP44-1414-0.80D



**Pin Function**

The TMP47P400V has MCU mode and PROM mode.

(1) MCU mode

The TMP47C200B/400B and the TMP47P400V are pin compatible (TEST pin for out-going test. Be fixed to low level).

(2) PROM mode

Pin Name	Input/Output	Functions	Pin Name (MCU Mode)
A11 to A9	Input	Address inputs	P11 to P13
A8 to A5			P20 to P23
A4			R72
A3 , A2			R42 , R43
A1 , A0			R50 , R51
I7 to I4	I/O	Data inputs / outputs	R83 to R80
I3 to I0			K03 to K00
$\overline{\text{PGM}}$	Input	Program control input	R92
$\overline{\text{CE}}$		Chip Enable input	R91
$\overline{\text{OE}}$		Output Enable input	R90
VPP	Power supply	+ 12.5 V / 5 V (Program supply voltage)	TEST
VCC		+ 5 V	VDD
VSS		0 V	VSS
P10	Output	Open or Be fixed to low level.	
R41 , R40	I/O	Be fixed to low level	
R53 , R52			
R63 to R60			
R70, R71, R73			
$\overline{\text{RESET}}$	Input	PROM mode setting pins. Be fixed to low level.	
$\overline{\text{HOLD}}$	Input		
XIN	Input	Resonator connecting pins.	
XOUT	Output		

### Operational Description

The following is an explanation of hardware configuration and operation in relation to the TMP47P400V. The TMP47P400V is the same as the TMP47C200B/400B except that an OTP is used instead of a Mask ROM.

## 1. Operation Mode

The TMP47P400V has an MCU mode and a PROM mode.

### 1.1 MCU Mode

The MCU mode is set by fixing the TEST / VPP pin at the "L" level. Operation in the MCU mode is the same as for the TMP47C200B/400B, except that the TEST / VPP pin does not have pull-down resistor and cannot be used open.

#### 1.1.1 Program Memory

The program storage area is the same as for the TMP47C200B/400B. Data conversion tables must be set in two locations when using the TMP47P400V to check TMP47C200B operation.




Figure 1-1. Program area (RAM)

Figure 1-2. Shared RAM address (RAM)

### 1.1.2 Data Memory

The TMP47P400V has 256 × 4-bit data memory. When using the TMP47P400V as a TMP47C200B evaluator, programming should be performed assuming that the RAM is assigned to addresses 00 to 0FH and 90 to FF<sub>H</sub> as show in Figure 1-2 by considering the application software evaluation.

## Electrical Characteristics

Absolute Maximum Ratings (V<sub>SS</sub> = 0 V)

Parameter	Symbol	Pins	Ratings	Unit
Supply Voltage	V <sub>DD</sub>		- 0.3 to 7	V
Program Voltage	V <sub>PP</sub>	TEST / VPP pin	- 0.3 to 13.0	V
Input Voltage	V <sub>IN</sub>		- 0.3 to V <sub>DD</sub> + 0.3	V
Output Voltage	V <sub>OUT1</sub>	Except sink open drain pin, but include R8	- 0.3 to V <sub>DD</sub> + 0.3	V
	V <sub>OUT2</sub>	Sink open drain pin except R8	- 0.3 to 10	
Output Current (per 1 pin)	I <sub>OUT1</sub>	P1, P2	30	mA
	I <sub>OUT2</sub>	R4 to R9	3.2	
Output Current (total all pin)	∑ I <sub>OUT1</sub>	P1, P2	120	mA
Power Dissipation [Topr = 70°C]	PD		600	mW
Soldering Temperature (time)	Tsld		260 (10 s)	°C
Storage Temperature	Tstg		- 55 to 125	°C
Operating Temperature	Topr		- 30 to 70	°C

*Note: The absolute maximum ratings are rated values which must not be exceeded during operation, even for an instant. Any one of the ratings must not be exceeded. If any absolute maximum rating is exceeded, a device may break down or its performance may be degraded, causing it to catch fire or explode resulting in injury to the user. Thus, when designing products which include this device, ensure that no absolute maximum rating value will ever be exceeded.*

Recommended Operating Conditions (V<sub>SS</sub> = 0 V, Topr = - 30 to 70°C)

Parameter	Symbol	Pins	Conditions	Min	Max	Unit
Supply Voltage	V <sub>DD</sub>		In the Normal mode	2.7	6.0	V
			In the HOLD mode	2.0		
Input High Voltage	V <sub>IH1</sub>	Except hysteresis input	V <sub>DD</sub> ≥ 4.5 V	V <sub>DD</sub> × 0.7	V <sub>DD</sub>	V
	V <sub>IH2</sub>	Hysteresis input		V <sub>DD</sub> × 0.75		
	V <sub>IH3</sub>		V <sub>DD</sub> < 4.5 V	V <sub>DD</sub> × 0.9		
Input Low Voltage	V <sub>IL1</sub>	Except hysteresis input	V <sub>DD</sub> ≥ 4.5 V	0	V <sub>DD</sub> × 0.3	V
	V <sub>IL2</sub>	Hysteresis input			V <sub>DD</sub> × 0.25	
	V <sub>IL3</sub>		V <sub>DD</sub> < 4.5 V		V <sub>DD</sub> × 0.1	
Clock Frequency	fc		V <sub>DD</sub> = 2.7 to 6.0 V	0.4	4.2	MHz

*Note: The recommended operating conditions for a device are operating conditions under which it can be guaranteed that the device will operate as specified. If the device is used under operating conditions other than the recommended operating conditions (supply voltage, operating temperature range, specified AC/DC values etc.), malfunction may occur. Thus, when designing products which include this device, ensure that the recommended operating conditions for the device are always adhered to.*

## DC Characteristics

(V<sub>SS</sub> = 0 V, T<sub>opr</sub> = -30 to 70°C)

Parameter	Symbol	Pins	Conditions	Min	Typ.	Max	Unit
Hysteresis Voltage	V <sub>HS</sub>	Hysteresis Input		—	0.7	—	v
Input Current	I <sub>IN1</sub>	Port K0, TEST, RESET, HOLD	V <sub>DD</sub> = 5.5 V, V <sub>IN</sub> = 5.5 V / 0 V	—	—	± 2	μA
	I <sub>IN2</sub>	Port R (open drain)					
Input Low Current	I <sub>IL</sub>	Port R (push-pull)	V <sub>DD</sub> = 5.5 V, V <sub>IN</sub> = 0.4 V	—	—	-2	mA
Input Resistance	R <sub>IN2</sub>	RESET		100	220	450	kΩ
Output Leakage Current	I <sub>LO</sub>	Ports P, R (open drain)	V <sub>DD</sub> = 5.5 V, V <sub>OUT</sub> = 5.5 V	—	—	2	μA
Output High Voltage	V <sub>OH</sub>	Port R (push-pull)	V <sub>DD</sub> = 4.5 V, I <sub>OH</sub> = -200 μA	2.4	—	—	V
Output Low Voltage	V <sub>OL2</sub>	Except XOUT, Port P	V <sub>DD</sub> = 4.5 V, I <sub>OL</sub> = 1.6 mA	—	—	0.4	V
Output Low Current	I <sub>OL1</sub>	Port P	V <sub>DD</sub> = 4.5 V, V <sub>OL</sub> = 1.0 V	—	30	—	mA
Supply Current (in the Normal mode)	I <sub>DD</sub>		V <sub>DD</sub> = 5.5 V f <sub>c</sub> = 4 MHz	—	2	4	mA
			V <sub>DD</sub> = 3.0 V f <sub>c</sub> = 4 MHz	—	1	2	mA
Supply Current (in the HOLD mode)	I <sub>DDH</sub>		V <sub>DD</sub> = 5.5 V	—	0.5	10	μA

Note 1: Typ. values show those at T<sub>opr</sub> = 25°C, V<sub>DD</sub> = 5 V.

Note 2: Input Current I<sub>IN1</sub>: The current through resistor is not included, when the pull-up / pull-down resistor is contained.

Note 3: Supply Current: V<sub>IN</sub> = 5.3 V / 0.2 V (V<sub>DD</sub> = 5.5 V), 2.8 / 0.2 V (V<sub>DD</sub> = 3.0 V)


AC Characteristics

( $V_{SS} = 0\text{ V}$ ,  $V_{DD} = 2.7\text{ to }6.0\text{ V}$ ,  $T_{opr} = -30\text{ to }70^\circ\text{C}$ )


Parameter	Symbol	Conditions	Min	Typ.	Max	Unit
Instruction Cycle Time	$t_{cy}$		1.9	–	20	$\mu\text{s}$
High Level Clock Pulse Width	$t_{WCH}$	External clock mode	80	–	–	ns
Low Level Clock Pulse Width	$t_{WCL}$					
Shift Data Hold Time	$t_{SDH}$		$0.5 t_{cy} - 0.3$	–	–	$\mu\text{s}$

Note: Shift Data Hold Time:

External circuit for  $\overline{\text{SCK}}$  pin and SO pin



Serial port (completion of transmission)



Recommended Oscillating Conditions

( $V_{SS} = 0\text{ V}$ ,  $V_{DD} = 2.7\text{ to }6.0\text{ V}$ ,  $T_{opr} = -30\text{ to }70^\circ\text{C}$ )


Recommended oscillating conditions of the TMP47P400V are equal to the TMP47C200B/400B's.

DC/AC Characteristics (PROM mode)

( $V_{SS} = 0\text{ V}$ )


(1) Read Operation

Parameter	Symbol	Condition	Min	Typ.	Max	Unit
Output Level High Voltage	$V_{IH4}$		$V_{CC} \times 0.7$	–	$V_{CC}$	V
Output Level Low Voltage	$V_{IL4}$		0	–	$V_{CC} \times 0.3$	V
Supply Voltage	$V_{CC}$		4.75	–	6.0	V
Programming Voltage	$V_{PP}$					
Address Access Time	$t_{ACC}$	$V_{CC} = 5.0 \pm 0.25\text{ V}$	–	–	350	ns



(2) High Speed Programming Operation

Parameter	Symbol	Condition	Min	Typ.	Max	Unit
Input High Voltage	$V_{IH4}$		$V_{CC} \times 0.7$	–	$V_{CC}$	V
Input Low Voltage	$V_{IL4}$		0	–	$V_{CC} \times 0.3$	V
Supply Voltage	$V_{CC}$		4.75	–	6.0	V
$V_{PP}$ Power Supply Voltage	$V_{PP}$		12.0	12.5	13.0	V
Programming Pulse Width	$t_{PW}$	$V_{CC} = 6.0 \pm 0.25$ V	0.95	1.0	1.05	ms





Typical Characteristics

